

Light Duty Stackers Specification

Machine Type		Fixed Wrapover Forks				Adjustable Forks		
B Raised Height	Operation	C/D O/A Height of Machine when forks Raised / Lowered	Reference	Lift Speed	Weight KG	Reference	Lift Speed	Weight KG
1830	Manual	2270/1395	ST-250-1830-M	33/stroke	106	ST-250-1830-M-ADJ	33/stroke	106
1830	Electric	2270/1395	ST-250-1830-E	6 sec / Meter	146	ST-250-1830-E-ADJ	6 sec / Meter	146
2450	Manual	2825 / 1650	ST-250-2450-M	40/stroke	136	ST-250-2450-M-ADJ	40/stroke	136
2450	Electric	2825 / 1650	ST-250-2450-E	6 sec / Meter	200	ST-250-2450-E-ADJ	6 sec / Meter	200
Load Centre		-	270		250			
Free Lift		-	Nil		Nil			
Closed Fork Height		A	90		85			
O/A W x L		E	665 x 1030		665 x 1030			
Fork Length		G	540		500			
Width Across Forks		H	560		635 max			
Fork W x D		-	110 x 50		50 x 20			
Width Between Legs		J	360		360			
Castor Wheels		-	125 dia, 1 braked (Nylon)		125 dia, 1 braked (Nylon)			
Load Roller Dia x L		-	80 x 50 (Nylon)		80 x 50 (Nylon)			
Turning Radius		F	950		950			

All dimensions are in mm unless otherwise shown

Optional Extras (Available on all models)

- **Steel Platform*** A x B = 540 x 570
- **Roller conveyor Platform*** Plastic Rollers) A x B = 540 x 570
- **Crane Jib + A = 500**
- **Straddle Width 1100 between legs**

* Fixed fork models only + Adjustable fork models only

